ESTA VILLA™

GLAZED PORCELAIN FLOOR - GLAZED CERAMIC WALL & MOSAIC with REVEAL IMAGING™



Everyday Style in a Durable Tile

floor • wall • countertop

Visually inspired by the soft look of natural stone but at a competitive price point. The Esta Villa collection closely mirrors the natural tones and depths of Rapolano Italian stone to create a remarkably realistic look. Choose from a palette of neutral color tones that create a sense of movement within each unique piece of tile.



ESTA VILLA**

GLAZED PORCELAIN FLOOR -GLAZED PORCELAIN FLOOR – GLAZED CERAMIC WALL & MOSAIC with REVEAL IMAGING™ $with \; \mathsf{REVEAL} \; \mathsf{IMAGING}^\mathsf{m}$

Glazed Porcelain Floor Tile





TERRACE BEIGE EV98



Glazed Ceramic Wall Tile





TERRACE BEIGE EV98

COTTAGE BROWN EV99

GARDEN WHITE EV97

ESTA VILLA M GLAZED PORCELAIN I LOGIN GLAZED CERAMIC WALL & MOSAIC with REVEAL IMAGING M

Glazed Ceramic Mosaics



GARDEN WHITE EV97 2 x 4 Brick-joint Mosaic



TERRACE BEIGE EV98 2 x 4 Brick-joint Mosaic



COTTAGE BROWN EV99 2 x 4 Brick-joint Mosaic

CREATIVE IDEAS

Jolor



GARDEN WHITE



TERRACE BEIGE



COTTAGE BROWN





STONE RADIANCE WHISPER GREEN BLEND SA5 I Stone/Glass Random Mosaic



NATURAL STONE DECORATIVE ACCENTS BRENTA BLEND DA87 I x I Mosaic Honed



METAL SIGNATURES AGED BRONZE MS11 4 x 12 Jardin Floor/Wall Border

$Backsplash\ Design\ Idea$



Backsplash features Cottage Brown 2 \times 4 brick-joint mosaic with Cristallo Glass in Smoky Topaz 3/4 \times 8 pencil rail and Intertwine in Energy 5/8 \times 2 glass mosaic with 5/8 \times 5/8 stone dot.

Pattern Ideas







BRICK GRID DIAMOND



ESTA VILLA M GLAZED PORCELAIN FLOOR - GLAZED CERAMIC WALL & MOSAIC with REVEAL IMAGING M

SIZES

		SQ.FT. CARTON	PCS. PER CARTON
18 x 18 Floor	(17-3/4" × 17-3/4") (45.2 cm × 45.2 cm)	18.00	8
I2 x 24 Floor	(11-11/16" × 23-5/8") (29.7 cm × 60 cm)	12.00	6
12 x 12 Floor	(11 13/16" x 11 13/16") (30.0 cm x 30.0 cm)	11.00	П
10 x 14 Wall	(9-27/32" × 13-31/32") (25.0 cm × 35.5 cm)	14.58	15
2 x 4 Mosaic	(11-7/8" × 12-7/8" sheet) (30.2 cm × 32.6 cm sheet)	10.00	12

RESIDENTIAL USAGE

	FLOORS	WALLS	COUNTERTOPS	EXTERIOR PATIOS	EXTERIOR POOL DECKS
_	F*	W	С	EP	

^{*}Wall tile only suitable for residential bathroom floors not subject to outside foot traffic.

COMMERCIAL USAGE

	INTERIOR			EXTERIOR	
	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL	RESIDENTIAL	COMMERCIAL
Floors/Patios*	✓	✓	✓	~	
Walls/Backsplashes	✓	✓	✓	~	✓
Countertops	~	✓	~	~	✓
Pool Decking					
Pool Linings	~	✓	~	~	✓

^{*}Floor tile and mosaics only.

Floor tile suitable for exterior floors (excluding pool decking) in freezing and non-freezing climates when proper installation methods are followed.

Mosaic tile suitable for exterior floors (excluding pool decking) in non-freezing climates when proper installation methods are followed.

Wall tile suitable for exterior walls in non-freezing climates when proper installation methods are followed.

NOTES

Since there is shade variation in all glazed ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Use of a latex modified thin-set is recommended for installation.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information, refer to "Factors to Consider" at http://daltile.com/factors-to-consider.cfm.

TRIM

ТҮРЕ	NUMBER	SIZE	PCS. PER CARTON
Floor Bullnose*	P-43C9	3 × 12	22
Wall Bullnose	S-4310	3 × 10	54
Wall Bullnose Corner	SN-4310	3 × 3	32

^{*} Floor Bullnose trim is intended to coordinate with floor field tile in the standard 90-degree installation position.

SHADE VARIATION



HIGH (V3)

Color variation from tile to tile and within each tile.

INSTALLATION

THICKNESS	GROUT JOINT RECOMMENDATION
5/16" Floor, Wall	3/16" Floor, 1/16" Wall,
& Mosaic	I/8" Mosaics

DYNAMIC C.O.F. (WET): 2

The higher the rating, the higher the slip resistance.

I < 0.42	Wall
2 ≥ 0.42	Floor & Mosaic

DURABILITY: 4

Flo	oor wear resistance
I	Residential Bathrooms
2	All Residential Areas
3	All Residential / Light Commercial
4	All Residential / Commercial

STATIC C.O.F. (WET): 2

	, ,
0.50 - 0.59	Wall
2 ≥ 0.60	Floor & Mosaic

TEST RESULTS

	ASTM#	FLOOR RESULT	MOSAIC RESULT	WALL RESULT
Water Absorption	C373	< 0.5%	< 3.0%	< 20.0%
Breaking Strength	C648	> 275 lbs.	> 250 lbs.	100 - 230 lbs.
Scratch Hardness	MOHS	8.0	8.0	4.0 - 6.5
Chemical Resistance	C650	Resistant	Resistant	Resistant
Dynamic C.O.F.	A137.1	Wet: ≥ 0.42	Wet: ≥ 0.42	Wet: <0.42%
Static C.O.F.	C1028	Wet: ≥ 0.60 Dry: ≥ 0.65	Wet: ≥ 0.60 Dry: ≥ 0.65	Wet: ≥ 0.50 Dry: ≥ 0.80
Abrasion Resistance	C1027	4	4	

Dynamic C.O.F. (Wet) value as measured by the DCOF AcuTest^{5M} helps to assess a product's suitability for a commercial environment. For more information, visit our website at www.daltile.com/DCOF.

ESTA VILLA™

GLAZED PORCELAIN & GLAZED WALL with REVEAL IMAGING $^{ imes}$







By their very design, Daltile products can help make it easier for you to earn LEED™ points and/or points towards many industry leading green home building programs. From using recycled material content to establishing manufacturing facilities within 500 miles of your project, we help ensure you don't have to compromise your design to be environmentally conscious. For detailed information, visit daltilegreenworks.com.













PRODUC