



THIS IS GREENFIBER® LOOSE FILL CELLULOSE INSULATION

Application Coverage Chart 30 lbs (13.61 kg) INS510LD
DO NOT ADD WATER TO THIS PRODUCT.

R-Value at 75° F Mean Temp. Valor de resistencia térmica (valor R) a 75 F de temperatura media	Minimum Thickness (inches) Espesor mínimo (en pulgadas)		Net Coverage (no adjustment for framing) Cobertura neta (sin compensación para el entramado)			Gross Coverage (based on 2"x 6" framing on 16" centers) Recubrimiento Bruto (Basado en armazón de 5.1 cm (2") x 15.2 cm (6") en centro de 40.64 cm (16"))	
	Initial Installed Thickness Espesor inicial instalado	Settled Thickness Espesor asentado	Maximum Sq. Ft. per Bag Metros Cuadrado máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados	Minimum Weight per Sq. Ft. Peso mínimo por pie cuadrado	Maximum Sq. Ft. per Bag Metros Cuadrado máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados
11	3.40	3.06	79.8	12.5	0.376	88.0	11.4
13	4.01	3.61	66.7	15.0	0.450	73.6	13.6
19	5.84	5.25	44.2	22.6	0.679	48.5	20.6
22	6.74	6.07	37.6	26.6	0.799	40.7	24.6
26	7.94	7.15	31.1	32.1	0.963	33.3	30.0
30	9.13	8.22	26.5	37.8	1.133	28.1	35.6
32	9.72	8.75	24.6	40.7	1.221	26.0	38.5
38	11.49	10.34	20.1	49.7	1.491	21.1	47.5
40	12.08	10.87	18.9	52.8	1.584	19.8	50.5
44	13.25	11.93	16.9	59.1	1.774	17.6	56.8
48	14.42	12.98	15.2	65.7	1.970	15.8	63.3
49	14.71	13.24	14.9	67.3	2.020	15.4	65.0
50	15.00	13.50	14.5	69.0	2.070	15.0	66.6
60	17.90	16.11	11.6	86.4	2.593	11.9	83.9

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 30 LBS USING A VOLUMATIC III, 3rd GEAR AND 8" GATE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1000 SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE APPLICATION OF SPECIFIED R-VALUE. THIS PRODUCT IS INTENDED FOR DRY APPLICATION ONLY. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTING CAN INFLUENCE ACTUAL COVERAGE. DO NOT ADD WATER TO THIS PRODUCT. MINIMUM NET WEIGHT IS 28.5 LBS.

Dry Dense Pack Sidewall Applications (DO NOT ADD WATER)			30 lbs. (13.61kg) INS510LD		
Thermal Resistance (R value) Resistencia térmica (R)	Framing Estructura	Installed Thickness (inches) Espesor instalado (pulgadas)	Minimum Wt. Per Square Foot lb/ft ² Peso mínimo por pie cuadrado lb/ft ²	Maximum Coverage Per Bag (Adjusted for Framing) ft ² /Bag Cobertura máxima por bolsa (con compensación para el entramado) ft ² /Bag	
				(16" oc)	(24" oc)
13	2x4	3.5	1.02	32.4	31.3
21	2x6	5.5	1.60	20.6	19.9

THIS COVERAGE CHART IS FOR DRY APPLICATIONS ONLY AND IS BASED ON THE KRENDL KS200, WITH MATERIAL APPLIED DRY. FOR MAXIMUM COVERAGE PER BAG (ADJUSTED FOR FRAMING), THE FRAMING FACTOR FOR 16" OC STUD SPACING IS 9.375%; FOR 24" OC STUD SPACING THE FRAMING FACTOR IS 6.25%.

READ THIS BEFORE YOU BUY

What you should know about R-values

This chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy. There are other factors to consider. The amount of the insulation you need depends on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel. To get the marked R-value, it is essential that this insulation be installed properly.

FOR MORE INFORMATION CONTACT GREENFIBER:

GreenFiber Corporate Office
 2500 Distribution Street, Suite 200
 Charlotte, NC 28203

(p) 800.228.0024 (f) 704.379.0685
 (e) greenfiber.info@greenfiber.com
 www.greenfiber.com

MANUFACTURING LOCATIONS:

Albany, NY
 Delphos, OH
 Norfolk, NE
 Phoenix, AZ
 Salt Lake City, UT
 Tampa, FL
 Waco, TX

